



Kinetic Polymers


(AN ISO 9001 - 2008 Certified Company)

D-13/2, Phase-1, Road No. 3, IDA., Jeedimetla, Hyderabad - 055. INDIA
Phones : 7207078344, 7207008277, Telefax : 040-23093957
Email : kineticpolymers@gmail.com / Website : www.kineticpolymers.com



Technical Specification of Antistatic PVC 3 Layer Mat

- | | | |
|---------------------------|---|--|
| 1. Material | : | Homogeneous Antistatic composition with black Conductive layer sandwiched between Two antistatic layers. |
| 2. Thickness | : | 2 mm $\pm$ 0.1mm |
| 3. Sound Reduction factor | : | 3 db for 2 mm thickness |
| 4. Inflammability | : | Self-extinguishing. |
| 5. Water absorption | : | At room temperature for 24 hours is Less than 0.1% |
| 6. Colour | : | Blue / Grey |
| 7. Length of Roll | : | 15 mtrs |
| 8. Width of Roll | : | 2 mtr |



ELECTRICAL PROPERTIES:

- | | | |
|-------------------------|---|--------------------------|
| 1). Surface Resistivity | : | 10^6 – 10^9 ohms/sq. |
| 2). Decay Time | : | Less than 2 seconds |

